

PULSAR

CAL. VD53 & VD54 CHRONOGRAPH

CALIBER OF THREE HANDS WITH THREE EYES
(MINUTES, 1/1 SECOND CHRONOGRAPH, 24-HOUR INDICATOR)

TIME/CALENDAR


- Hour, minute and second hands
- Date displayed in numerals (VD53 only)

STOPWATCH

- Measures up to 60 minutes in one second increments

ENGLISH

English






English

TIME SETTING

- Before setting the time, check that the stopwatch measurement is stopped.




CROWN

- 1 Pull out to first click, and turn clockwise until the previous day's date appears (VD53 only).
- 2 Pull out to second click when the second hand is at the 12 o'clock position. The second hand will stop on the spot. And advance the hour and minute hands by turning the crown.
- 3 Turn clockwise until the desired date appears (VD53 only).
- 4 Turn to set the hour and minute hands.
- 5 Push back in to normal position in accordance with a time signal.

STOPWATCH

- The stopwatch can measure up to 60 minutes in one second increments.
- The measured time is indicated by the STOPWATCH hands that move independently of the center and 24-hour hands.
- Before using the stopwatch, be sure to check that the crown is set at the normal position and that the STOPWATCH hands are reset to the "0" position.

** If the STOPWATCH hands do not return to the "0" position when the stopwatch is reset, follow the procedure in "STOPWATCH HAND POSITION ADJUSTMENT".*



Standard measurement



Accumulated elapsed time measurement



Split time measurement



NOTES ON OPERATING THE WATCH

TIME SETTING

- Do not press any button when the crown is at the second click position, as this will move the STOPWATCH hands.
- When the time is set, the 24-hour hand move correspondingly with the hour and minute hands.
- When setting the hour hand, check that the 24-hour hand is correctly set.
- When setting the minute hand, first advance it 4 to 5 minutes ahead of the desired time and then turn it back to the exact minute.

Date setting (VD53 only)

- It is necessary to adjust the date on the first day after a 30-day month and February.
- Do not set the date between 9:00 p.m. and 1:00 a.m., as the date may not change properly. If it is necessary to set the date during that period of time, first change the time to any time outside of this period, set the date, and then reset to the correct time.

STOPWATCH

- Restart and stop of the stopwatch can be repeated by pressing button A.
- Measurement and release of split time can be repeated by pressing button B.

BATTERY CHANGE

2
Years

Battery life : Approx. 2 years

Battery : SEIKO SR920SW

- *If the stopwatch is used for more than 2 hours a day, the battery life may be less than the specified period.*
- *As the battery is inserted at the factory to check the function and performance of the watch, its actual life once in your possession may be less than the specified period.*
- *When the battery expires, be sure to replace it as soon as possible to prevent any malfunction.*

- *We recommend that you contact an AUTHORIZED PULSAR DEALER for battery replacement.*
- *After the battery is replaced with a new one, adjust the stopwatch hand position and set the time/calendar.*


● **Battery life indicator**

When the battery nears its end, the second hand moves at two-second intervals instead of normal one-second intervals. In that case, have the battery replaced with a new one as soon as possible.

- * *The watch remains accurate while the second hand is moving at two-second intervals.*

● Necessary procedure after battery change

After the battery is replaced with a new one, or in case any of the hands should move improperly, follow the procedure below to reset the STOPWATCH hands to “0” position.



* The STOPWATCH minute hand moves correspondingly with the STOPWATCH second hand.

* The STOPWATCH hands move quickly if the respective buttons are kept pressed.

CROWN

Pull out to second click.

A AND B

Press and hold simultaneously for 2 seconds or longer.

** The STOPWATCH second hand turns counter clockwise, and then returns to where it was.*

A OR B

Press to reset the STOPWATCH second and minute hands to the “0” position.

*A: The hands move counterclockwise.
B: The hands move clockwise.*

CROWN

Turn to set the time.

CROWN

Push back in to normal position.



WARNING

- Do not remove the battery from the watch.
- If it is necessary to take out the battery, keep it out of the reach of children. If a child swallows it, consult a doctor immediately.
- Never short-circuit, tamper with or heat the battery, and never expose it to fire. The battery may burst, become very hot or catch fire.



CAUTION

- The battery is not rechargeable. Never attempt to recharge it, as this may cause battery leakage or damage to the battery.

TO PRESERVE THE QUALITY OF YOUR WATCH

WATER RESISTANCE

● Non-water resistant



If "WATER RESISTANT" is not inscribed on the case back, your watch is not water resistant, and care should be taken not to get it wet as water may damage the movement. If the watch becomes wet, we suggest that you have it checked by an AUTHORIZED PULSAR DEALER or SERVICE CENTER.

● Water resistance (3 bar)



If "WATER RESISTANT" is inscribed on the case back, your watch is designed and manufactured to withstand up to 3 bar, such as accidental contact with splashes of water or rain, but it is not designed for swimming or diving.

● Water resistance (5 bar)*



If "WATER RESISTANT 5 BAR" is inscribed on the case back, your watch is designed and manufactured to withstand up to 5 bar and is suitable for swimming, yachting and taking a shower.

● Water resistance (10 bar/15 bar/20 bar)*



If "WATER RESISTANT 10 BAR", "WATER RESISTANT 15 BAR" or "WATER RESISTANT 20 BAR" is inscribed on the case back, your watch is designed and manufactured to withstand up to 10 bar/15 bar/20 bar and is suitable for taking a bath, shallow diving, but not for scuba diving. We recommend that you wear a PULSAR Diver's watch for scuba diving.

English

